

Portable Cooling and Heating

9,000 to 12,000 BTUH Cooling



Unlike a single hose system, our dual hose unit operates like a traditional air conditioner. It uses outside air to carry away heat collected from the room without exhausting cool air, providing maximum comfort and efficiency.

Cool or heat a room without any ductwork or special wiring—and move the unit from room to room as needed! Our portable units are ideal for situations where a window isn't available or can't handle a room A/C unit, or where temporary cooling is needed—apartments, bedrooms, cottages, warehouses, offices, historical properties. They can also be used to supplement the central heating and/or cooling system, or to save energy by conditioning only the room being used.

All units have cool, heat, dehumidify and air circulation modes, and move easily thanks to casters and built-in handles. Dual flexible hoses are 71" long; hose hook-up is not needed for heating, dehumidification or air circulation (fan only) modes.



PE-91A and PE-121A

PE-91A/PE-121A FEATURES

- Separate hot air exhaust and air inlet hoses
- Disposes of its own condensate under most conditions—there's no bucket to empty; auto stop for overflow protection as a safeguard
- Easy-access air filter is washable
- Louvers can be set for oscillation of horizontal airflow: they're motorized to adjust positioning
- Electronic controls have soft-touch keypad
- Programmable wireless remote control shows the same display as the unit's LCD
- 24-Hour on/off timer can be used to save on energy consumption when you're not home
- Auto restart reverts to last setting following a power outage
- Sliding adapters that fit a variety of window sizes (double-hung and slider) and patio doors make installation fast and easy



MODES

- **Auto**—automatically sets mode and fan based on room temperature
- **Cooling**—automatic or manually set temperature
- **Heating**—for supplemental heat only
- **Dehumidify**—removes excess moisture for greater comfort
- **Fan Only**—three cooling, three fan speeds



Warranty five years on compressor, one year on parts.

Model	Cooling Cap. BTUH	Approx. Sq. Ft. Cooling	EER	Humidity Removal/Pts/Hr	Heating Cap. BTUH	Max. CFM	Amps Cooling	Amps Heating	Dimensions H x W x D (in.)	Shipping Wt. (lbs.)
PE-91A	9,000	400	8.5	2.5	3412	210	10.0	8.7	31.9 x 19.1 x 19.4	95
PE-121A	12,000	550	8.5	2.8	4266	210	11.5	10.87	31.9 x 19.1 x 19.4	97



800-966-7100