

# HEAT WAVE™ PORTABLE ELECTRIC SALAMANDER

**(800)966-7100**

**RANKIN**  
LEADERS IN TEMPORARY CLIMATE SOLUTIONS™

- Safety yellow heater enclosure with safety screens on both air intake and output openings
- Optional 25' long SO type cord, ready for plug attachment is available for each model
- Long-life finned tubular heating elements
- Thermostat adjustment 40° to 100° F
- High-limit thermal cutoff switch
- CFM Ratings:  
800 CFM - 10/15kW Units  
1100 CFM - 30kW units
- Magnetic contactor
- Fan only operation feature



AVERAGE MINUTES TO ACHIEVE TEMPERATURE RISE*						
BUILDING SIZE:	1000 SQ. FEET		1500 SQ. FEET		2000 SQ. FEET	
	TEMP RISE		TEMP RISE		TEMP RISE	
HEATER:	20 °F	40 °F	20 °F	40 °F	20 °F	40 °F
	10 KW	70 min	140 min	105 min	210 min	---
	15 KW	47 min	94 min	71 min	142 min	94 min
30 KW	23 min	46 min	35 min	70 min	47 min	94 min

\* Based on a 15' ceiling height - low or ceiling height will reduce time required

UPC	MODEL	KW	BTU's	VOLTS	PH	AMPS	TEMP RISE	WT.
686334								
886017	FES-1520-3A	15	51195	208	3	42	45°F	66 lbs.
886079	FES-1524-1A	15	51195	240	1	63	45°F	69 lbs.
886024	FES-1524-3E	15	51195	240	3	36	45°F	65 lbs.
886031	FES-1548-3E	15	51195	480	3	18	45°F	65 lbs.
886055	FES-3048-3A	30	102390	480	3	36	90°F	83 lbs.

OPTIONAL 25' POWER CORD	
UPC 686334	TYPE
316408	6/4 SO
880534	4/3 SO
316408	6/4 SO
316422	12/4 SO
316408	6/4 SO

**10KW - 240V - 1 PHASE FACTORY PRE-WIRED MODEL WITH 10 FT. CABLE & STRAIGHT BLADE RANGE PLUG FOR USE WITH A STANDARD RANGE OUTLET.**

UPC	MODEL	KW	BTU's	VOLTS	PHASE	AMPS	TEMP RISE	WT.
686334								
200134	FES-1024-1CA	10	34130	240	1	42	30°F	60 lbs.



## WALL / CEILING MOUNT ELECTRIC SALAMANDER

CEILING MOUNT



- All YES-Series units can be mounted to either a Wall or Ceiling Surface
- Yoke and Bracket included with each YES Unit
- All units are designed for direct wire installation

WALL MOUNT



UPC	MODEL	KW	BTU's	VOLTS	PHASE	AMPS	TEMP RISE	WT.	LIST
686334									
886086	YES-1520-3A	15	51195	208	3	42	45°F	60 lbs.	<b>1350</b>
886185	YES-1524-1A	15	51195	240	1	63	45°F	60 lbs.	<b>1350</b>
886093	YES-1524-3E	15	51195	240	3	36	45°F	60 lbs.	<b>1350</b>
886109	YES-1548-3E	15	51195	480	3	18	45°F	60 lbs.	<b>1350</b>
886123	YES-3048-3A	30	102390	480	3	36	90°F	72 lbs.	<b>2130</b>